

# PREMIER

## HYDRAULIC JACK

### GENERAL PURPOSE HYDRAULIC JACK

Single Acting, Plain Ram, Spring Return Type

Capacity: 5 – 200 Ton | Stroke: 50 – 250mm | Max. Pressure: 700 Bar



Capacity (TON)	Close Height	Stroke	Body Dia.	Bore Dia.	Ram Dia.	Model No.
10 Ton	150mm	50mm	80mm	63mm	50mm	PJ10-050
	200mm	100mm	80mm	63mm	50mm	PJ10-100
	250mm	150mm	80mm	63mm	50mm	PJ10-150
	300mm	200mm	80mm	63mm	50mm	PJ10-200
20 Ton	200mm	100mm	89mm	63mm	50mm	PJ20-100
	250mm	150mm	89mm	63mm	50mm	PJ20-150
	300mm	200mm	89mm	63mm	50mm	PJ20-200
30 Ton	150mm	50mm	105mm	75mm	60mm	PJ30-050
	200mm	100mm	105mm	75mm	60mm	PJ30-100
	250mm	150mm	105mm	75mm	60mm	PJ30-150
	300mm	200mm	105mm	75mm	60mm	PJ30-200
50 Ton	200mm	50mm	130mm	100mm	80mm	PJ50-050
	225mm	100mm	130mm	100mm	80mm	PJ50-100
	250mm	100mm	130mm	100mm	80mm	PJ50S-100
	300mm	150mm	130mm	100mm	80mm	PJ50-150
100 Ton	200mm	50mm	190mm	140mm	100mm	PJ100-050
	250mm	100mm	190mm	140mm	100mm	PJ100-100
	300mm	150mm	190mm	140mm	100mm	PJ100-150
	350mm	200mm	190mm	140mm	100mm	PJ100-200
200 Ton	350mm	150mm	250mm	190mm	150mm	PJ200-150

- Also Available in Double Acting. (Specs. May differ)
- Also Available as per Set, with Hand Pump set.
- Also Available as per Requirement. (Customized as per specs. Provided).
- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits. Use at 80% of rating as safe practice.

### Technical Specification for Hand Pump set: - Working Pressure 700bar

Hand Pump (Double Plunger) 10Ltr. Oil Capacity Or  
Hand Pump (Single Plunger) 1Ltr. Oil Capacity

2mtr. Long High-Pressure Hose Pipe with both end fittings

Pressure Gauge 1000 Kg/Cm<sup>2</sup>



Pressure Gauge



High-Pressure Hose Pipe