

PREMIER

HYDRAULIC JACK

HYDRAULIC HOLLOW RAM JACK

Single Acting, Plain Ram, Spring Return Type

Capacity: 10 – 100 Ton | Stroke: 50 – 150mm | Max. Working Pressure: 700 Bar



Hand Pumps

Cap. (TON)	Close Height	Stroke	Body Dia.	Bore Dia.	Ram Dia.	C' Hole Dia.	Weight (Approx)	Model No.
10 Ton	165mm	50mm	75mm	60mm	50mm	20mm	4.6 Kg.	PJH10-050
	190mm	75mm	75mm	60mm	50mm	20mm	5.3 Kg.	PJH10-075
	215mm	100mm	75mm	60mm	50mm	20mm	6.0 Kg.	PJH10-100
20 Ton	170mm	50mm	105mm	85mm	75mm	27mm	10.5 Kg.	PJH20-050
	220mm	100mm	105mm	85mm	75mm	27mm	13.5 Kg.	PJH20-100
	270mm	150mm	105mm	85mm	75mm	27mm	16.0 Kg.	PJH20-150
30 Ton	195mm	50mm	115mm	95mm	80mm	33mm	13.0 Kg.	PJH30-050
	220mm	75mm	115mm	95mm	80mm	33mm	14.5 Kg.	PJH30-075
	245mm	100mm	115mm	95mm	80mm	33mm	16.0 Kg.	PJH30-100
	295mm	150mm	115mm	95mm	80mm	33mm	19.0 Kg.	PJH30-150
50 Ton	230mm	75mm	150mm	125mm	100mm	42mm	25.0 Kg.	PJH50-075
	255mm	100mm	150mm	125mm	100mm	42mm	27.0 Kg.	PJH50-100
60 Ton	245mm	75mm	165mm	135mm	110mm	54mm	32.0 Kg.	PJH60-075
	270mm	100mm	165mm	135mm	110mm	54mm	35.0 Kg.	PJH60-100
	320mm	150mm	165mm	135mm	110mm	54mm	40.5 Kg.	PJH60-150
100 Ton	270mm	75mm	215mm	180mm	150mm	77mm	58.0 Kg.	PJH100-075
	295mm	100mm	215mm	180mm	150mm	77mm	62.0 Kg.	PJH100-100

- Also Available as per Requirement. (Customized as per specs. Provided).
- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits. Use at 80% of rating as safe practice.



Pressure Gauge



Hose Pipe