

PREMIER

HYDRAULIC JACK

LOW HEIGHT HYDRAULIC JACK

Single Acting, Plain Ram, Spring Return Type

Capacity: 10 – 200 Ton | Stroke: 30 – 60mm | Max. Pressure: 700 Bar



Hand Pump

Model No.	Capacity (Ton)	Close Height	Stroke	Body OD.	Bore Dia.	Ram Dia.	Weight (Approx)
PJL10-30	10 Ton	90mm	30mm	70mm	45mm	35mm	2.5 Kg.
PJL20-50	20 Ton	115mm	50mm	90mm	63mm	50mm	5 Kg.
PJL30-50	30 Ton	120mm	50mm	100mm	75mm	60mm	6 Kg.
PJL50-60	50 Ton	125mm	60mm	130mm	100mm	80mm	11 Kg.
PJL75-60	75 Ton	145mm	60mm	155mm	120mm	95mm	18.5 Kg.
PJL100-60	100 Ton	150mm	60mm	180mm	140mm	110mm	23.5 Kg.
PJL150-60	150 Ton	165mm	60mm	220mm	170mm	140mm	43 Kg.
PJL200-60	200 Ton	200mm	60mm	255mm	200mm	160mm	66 Kg.

- Light Weight, Low Profile Design for use in Confined Spaces.
- Also Available as per Set, with Hand Pump.
- Female Coupler & dust cap provided on all models.
- Also Available as per Requirement. (Customized as per specs. Provided).
- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits. Use at 80% of rating as safe practice.

Technical Specification for Hand Pump set: - Working Pressure 700bar

Hand Pump (Single Plunger) 1Ltr. Oil Capacity Or

2mtr. Long High-Pressure Hose Pipe with both end fittings

Pressure Gauge 1000 Kg/Cm²



Pressure Gauge



Hose Pipe